

Maintenance Oil

Page 1 of 2

Product:

Quick-Step Maintenance Oil White and Quick-Step Maintenance Oil Natural are solvent free maintenance products suitable for the yearly maintenance of Quick-Step oiled wood floors.

Technical data:

Base	Oil based
Curing system	Physical drying
 Consistency Colour Density Drying time* 	 fluid white or transparant Approx. 886 g/cm³ 24h, do not charge during this period and do not treat with water.
Application rate	75 m² per liter

^{*} This varies according to ambient conditions such as temperature, humidity etc.

Characteristics:

- Does not increase gloss level of the floor
- Repairs light damaged areas and walking lanes
- Feeds the floor
- Low consumption/m²
- Very low emission
- Solvent-free
- Product is made according to Decopaint guidelines 2010
- Product complies with ARBO legislation

Preparation:

With Hardwaxoil or Wax Oil treated wood:

remove soap rests with pure water and let dry. Use an intensive cleaner if heavily soiled.

Instructions:

Stir well before use. Apply a thin layer of Maintenance Oil

and let impregnate for a few minutes. Afterwards

Use a wood floor polisher to dispense the product or wipe the surface dry with a clean and dry cloth.

Do not charge during first 24 hours! During this period, do not treat with water.

After treatment:

It is recommended to treat the floor every year

Safety precautions:

Used rags and pads can be self-combustible. Put them in water after use.

R66 Repeated exposure may cause skin dryness or cracking.

S2 Keep out of the reach of children.

S23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

S24 Avoid contact with skin.

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well-ventilated areas.

P99 Contains 2-butanone oxime; phthalic anhydride. May produce an allergic reaction

B-8710 Wielsbeke, Tel.: 0032 (0)56-67.52.20 www.quick-step.com